



Chain No.	节距 Pitch						滚子直径 Roller diameter	销轴直径 Pin diameter	套筒直径 Bush diameter	
	P						d1 max mm	d2 max mm	d3 max mm	
	mm									
ZE 40	50.8	63.5	76.2	88.9	101.6	127.0	152.4	31.75	14.0	17.0
ZE 100	76.2	88.9	101.6	127.0	152.4	177.8	203.2	47.50	19.0	23.0
ZE 160	101.6	127.0	152.4	177.8	203.2	228.6	254.0	66.70	26.9	33.0
ZE 300	152.4	177.8	203.2	254.0	304.8	-	-	88.90	32.0	38.0

Chain No.	内节内宽 Width between inner plates	销轴长度 Pin length		链板高度 Plate depth		链板厚度 Plate thickness	抗拉强度 Tensile strength	
	b1 min mm	L max mm	Lc max mm	h2 max mm	h max mm	t/T max mm	Q min kN/bf	*Q min kN/bf
ZE 40	15.0	37.0	40.5	40.0	27.0	4.0	40.0/9091	60.0/13636
ZE 100	19.0	45.0	50.5	50.0	30.0	5.0/4.0	100.0/22725	160.0/36360
ZE 160	26.0	58.0	63.5	70.0	45.0	7.0/5.0	160.0/36360	200.0/45454
ZE 300	38.0	84.0	94.0	90.0	60.0	10.0/8.0	300.0/68175	380.0/86362

*Q 表示热处理后的抗拉强度
*Q denotes the tensile strength after hardened